

## POLYURETHANE 98 MB-LONGLIFE® SPIRAL HOSE

Spirals made of PU 98 MB-LONGLIFE®. Excellent elastic memory and longevity for a product that was born to work under stress.

### FEATURES

Foreign base polyurethane spirals of the **MB-LONGLIFE** series®. Their **excellent twisting resistance, excellent abrasion resistance and exceptional working memory** make them the ideal choice for projects that require repeated tube bends and twists.

### SECTORS

INDUSTRIAL

### APPLICATIONS

INDUSTRIAL AUTOMATION

VACUUM

MACHINE TOOLS

ROBOTICS

CABLE CARRIER CHAIN



## Products

Part number	Inner diameter (iØ)	Outer diameter (oØ)	Wall thickness	Standard colors	Material length	Working length	Retracted length	Turns n	Tale A	Tale B	winding Ø	outer Ø
SPU4X6X2C	3.8 mm	6 mm	1.1 mm	A	2 m	1.5 m	138 mm	22 N	100 mm	100 mm	20 mm	32 mm
SPU4X6X4C	3.8 mm	6 mm	1.1 mm	N A	4 m	3 m	296 mm	47 N	100 mm	100 mm	20 mm	32 mm
SPU5.5X8X2.5C	5.5 mm	8 mm	1.25 mm	A	2.5 m	2 m	151 mm	18 N	120 mm	500 mm	25 mm	41 mm
SPU5.5X8X5C	5.5 mm	8 mm	1.25 mm	A	5 m	4 m	362 mm	43 N	120 mm	500 mm	25 mm	41 mm
SPU5.5X8X7.5C	5.5 mm	8 mm	1.25 mm	A	7.5 m	6 m	564 mm	67 N	120 mm	500 mm	25 mm	41 mm
SPU5.5X8X10C	5.5 mm	8 mm	1.25 mm	A	10 m	7.5 m	766 mm	91 N	120 mm	500 mm	25 mm	41 mm
SPU5.5X8X12.5C	5.5 mm	8 mm	1.25 mm	A	12.5 m	9.5 m	976 mm	116 N	120 mm	500 mm	25 mm	41 mm
SPU6.5X10X2.5C	6.5 mm	10 mm	1.75 mm	A	2.5 m	2 m	126 mm	12 N	120 mm	500 mm	40 mm	60 mm
SPU6.5X10X5C	6.5 mm	10 mm	1.75 mm	A	5 m	4 m	294 mm	28 N	120 mm	500 mm	40 mm	60 mm
SPU6.5X10X7.5C	6.5 mm	10 mm	1.75 mm	A	7.5 m	6 m	463 mm	44 N	120 mm	500 mm	40 mm	60 mm
SPU6.5X10X10C	6.5 mm	10 mm	1.75 mm	N A	10 m	7.5 m	631 mm	60 N	120 mm	500 mm	40 mm	60 mm
SPU6.5X10X12.5C	6.5 mm	10 mm	1.75 mm	A	12.5 m	9.5 m	800 mm	76 N	120 mm	500 mm	40 mm	60 mm
SPU8X12X2.8C	8 mm	12 mm	2 mm	N A	2.5 m	2 m	126 mm	10 N	120 mm	500 mm	50 mm	74 mm
SPU8X12X5C	8 mm	12 mm	2 mm	A	5 m	4 m	290 mm	23 N	120 mm	500 mm	50 mm	74 mm

Part number	Inner diameter (iØ)	Outer diameter (oØ)	Wall thickness	Standard colors	Material length	Working length	Retracted length	Turns n	Tale A	Tale B	winding Ø	outer Ø
SPU8X12X7.5C	8 mm	12 mm	2 mm	A	7.5 m	6 m	454 mm	36 N	120 mm	500 mm	50 mm	74 mm
SPU8X12X10C	8 mm	12 mm	2 mm	A AM	10 m	7.5 m	618 mm	49 N	120 mm	500 mm	50 mm	74 mm
SPU8X12X12.5C	8 mm	12 mm	2 mm	A	12.5 m	9.5 m	770 mm	61 N	120 mm	500 mm	50 mm	74 mm
SPU8X12X15C	8 mm	12 mm	2 mm	A	15 m	11.5 m	934 mm	74 N	120 mm	500 mm	50 mm	74 mm

**PRESSURE/TEMPERATURE**

Operating temperature: from -40°C to 70°C

Safety factor on working pressure: 3:1

Here on the side: Graph of pressure drop expressed as a % in relation to temperature

