Mebra Plastik Italia s.p.a.
via Tibet 23/25 Busto Arsizio (VA) 21052
Tel: 0331 344005
E-mail: mebra@mebra.it

NOT SINTERED PTFE TAPE



PTFE tape is used as a sealing element for threads. Resistant to heat and chemical solvents.

FEATURES

The unsintered P.T.F.E tape is mainly used as a **sealing element for threads. Resistant to most of the known chemical compounds and solvents**, the PTFE tape can be used in a temperature range between -200 ° C and + 260 ° C. It has a **low coefficient of friction and is odorless, tasteless and insoluble**. The tape is normally packaged in plastic reels. It consists of virgin PTFE resin and is obtained through a process called **"Paste Extrusion".**

SECTORS

FOOD **AUTOMOTIVE** **INDUSTRIAL**

Mebra Plastik Italia s.p.a.
via Tibet 23/25 Busto Arsizio (VA) 21052
Tel: 0331 344005
E-mail: mebra@mebra.it

ADDITIONAL INFO

PRODUCT DETAILS

	External hose Ø (mm)	Length (m)	Width (mm)	Thickness(mm)	Qty (pcs.)
MCNP12076	less than 25	12	12	0.075	10
MCNP1200	25 to 40	12	12	0.1	10